

# Caravan and Automotive Cables

## MULTICORE AUTO CABLES

NO. OF CORES	CONDUCTOR CROSS SECTION mm <sup>2</sup>	NOMINAL CURRENT RATING AMPS	OVERALL DIAMETER	SHEATH COLOUR
5	5 x 0.75	5 x 14.0	6.3mm	BLACK
7	7 x 0.5	7 x 11.0	7.0mm	BLACK
7	7 x 0.75	7 x 14.0	6.8mm	BLACK
7	7 x 1.5	7 x 21.0	7.8mm	BLACK
7	6 x 1.0 + 1 x 2.0	6 x 16.5 + 1 x 25.0	7.8mm	BLACK
7	6 x 1.5 + 1 x 2.5	6 x 21.0 + 1 x 29.0	10.1mm	BLACK / SLATE
8	7 x 1.0 + 1 x 2.0	7 x 16.5 + 1 x 25.0	8.5mm	BLACK
12	7 x 1.5 + 5 x 2.5	7 x 21.0 + 5 x 29.0	13.0mm	BLACK
13	8 x 1.5 + 5 x 2.5	8 x 21.0 + 5 x 29.0	12.3mm	BLACK

**Core Colours:-** 5 CORE - BROWN, GREEN, RED, WHITE, YELLOW

**Core Colours:-** 7 CORE - BROWN, GREEN, RED, WHITE, YELLOW, BLUE, BLACK

**Core Colours:-** 8 CORE - BROWN, GREEN, RED, WHITE, YELLOW, BLUE, BLACK, PURPLE

**Core Colours:-** 12 CORE - BROWN, GREEN, RED, WHITE, YELLOW, BLUE, BLACK, ORANGE, RED/BROWN, WHITE/BLUE, WHITE/GREEN, BLUE/BROWN

**Core Colours:-** 13 CORE - BROWN, GREEN, RED, WHITE, YELLOW, BLUE, BLACK, ORANGE, PINK, GREY, WHITE/BLACK, WHITE/BLUE, WHITE/RED

Thin Wall Auto Cables to ISO 6722 Class B. Where applicable plain copper conductors – PVC insulated and sheathed. Delivery information – 100m coils.

## TWIN FLAT AUTO CABLES

CONDUCTOR SPECIFICATION	CROSS SECTION	NOMINAL CURRENT RATING AMPS	OVERALL DIAMETER
2 x 24/0.20mm	2 x 0.75mm	14.0 AMPS	3.5 x 5.5mm
2 x 32/0.20mm	2 x 1.0mm	16.5 AMPS	3.5 x 5.5mm
2 x 21/0.30mm	2 x 1.5mm	21.0 AMPS	3.8 x 6.6mm
2 x 28/0.30mm	2 x 2.0mm	25.0 AMPS	3.8 x 6.6mm
2 x 35/0.30mm	2 x 2.5mm	29.0 AMPS	4.4 x 7.6mm
2 x 44/0.30mm	2 x 3.0mm	33.0 AMPS	4.4 x 7.6mm
2 x 65/0.30mm	2 x 4.5mm	42.0 AMPS	5.7 x 9.5mm

Thin Wall Auto Cables to ISO 6722 Class B.  
Where applicable plain copper conductors – PVC insulated and sheathed.  
Delivery information – standard reel lengths 100m.

## SINGLE CORE AUTO CABLES

CONDUCTOR SPECIFICATION	CROSS SECTION	NOMINAL CURRENT RATING	OVERALL DIAMETER
16/0.20mm	0.5mm	11.0 AMPS	1.7mm
24/0.20mm	0.75mm	14.0 AMPS	1.9mm
32/0.20mm	1.0mm	16.5 AMPS	2.1mm
21/0.30mm	1.5mm	21.0 AMPS	2.4mm
28/0.30mm	2.0mm	25.0 AMPS	2.8mm
35/0.30mm	2.5mm	29.0 AMPS	3.0mm
44/0.30mm	3.0mm	33.0 AMPS	3.4mm
65/0.30mm	4.5mm	42.0 AMPS	4.1mm

Thin Wall Auto Cables to ISO 6722 Class B.

Where applicable plain copper conductors with PVC insulation.

Delivery information – all the above standard 100m and 500m Lengths.

Although every effort has been made to ensure the accuracy of specifications at the time of this publication, specifications for products described are subject to change without notice.

This publication has been issued for information purposes only and does not necessarily show stock availability.

For delivery information please contact Webro sales on: +44 (0)115 9724483 or email: [info@webro.com](mailto:info@webro.com)