




# Weblite Fibre Central Loose Tube




Indoor Optical Fibre




Non-metallic



Universal Central Loose Tube



Universal Unitube up to 24 fibres



Universal Unitube

## WEBLITE CENTRAL LOOSE TUBE, CORRUGATED STEEL TAPE AND TIGHT BUFFER CABLES

FIBRE COUNT	CENTRAL LOOSE TUBE		CORRUGATED STEEL TAPE		TIGHT BUFFER	
	OUTER DIAMETER Approx. (mm)	NET WEIGHT (Kg/Km)	OUTER DIAMETER Approx. (mm)	NET WEIGHT (Kg/Km)	OUTER DIAMETER Approx. (mm)	NET WEIGHT (Kg/Km)
2 - 12	5.8	40	10.5	127	4.8 - 6.5	22 - 43
12 - 24	7.2	55	10.5	127	6.5 - 8.3	43 - 67

### CENTRAL LOOSE TUBE DESCRIPTION

12-24 fibres contained within a single gel filled tube. Water blocking glass yarn strength members – Universal Black LSZH sheath.

### CORRUGATED STEEL TAPE ARMOUR DESCRIPTION

Up to 24 fibres contained within a single gel filled tube. Water blocking glass yarn strength elements. Corrugated steel tape armour – Blue LSZH outer sheath.

### PREMISE DISTRIBUTION DESCRIPTION

Up to 24 fibres with water blocking glass yarn strength elements in one – Orange LSZH outer sheath.

## ALL THE ABOVE

FIBRE TYPE (size $\mu\text{m}$ )	FIBRE CLASS
Multimode (62.5/125)	OM1
Multimode (50/125)	OM2
Multimode (50/125)	OM3
Multimode (50/125)	Enhanced OM3* - Capable of 10Gbit/s over 550m
Singlemode (9/125)	OS1
Singlemode (9/125)	OS1 & OS2 - Low Water Peak

Although every effort has been made to ensure the accuracy of specifications at the time of this publication, specifications for products described are subject to change without notice.

This publication has been issued for information purposes only and does not necessarily show stock availability.

For delivery information please contact Webro sales on: +44 (0)115 9724483 or email: [info@webro.com](mailto:info@webro.com)