

Technical Document
WEB240 50ohm Low Loss Coaxial Cable
PE Black

webro

Part Number: 140240F-BLK

Description: WEB240 50ohm Low Loss Coaxial
Cable PE Black



Product Construction

Conductor Material	:	Plain Annealed Copper
Conductor Stranding	:	Solid, 1/1.42mm
Dielectric Material	:	Foam Polyethylene (FPE)
Dielectric Diameter	:	3.81mm ± 0.15
Screening 1	:	Overall Bonded Aluminium Foil
Screening 1 Coverage	:	> 100%
Screening 2	:	Tinned Copper Wire Braid
Screening 2 Coverage	:	> 90% ± 3
Sheath Material	:	Polyethylene (PE)
Sheath Colour	:	Black



Mechanical Characteristics

Overall Diameter	:	6.1mm ± 0.15mm	
Temperature Range	:	Fixed -40°C to +70°C	Flexing -40°C to +70°C
Bend Radius	:	10 x Overall Diameter	
Weight	:	61kg/km	

Electrical Characteristics

Inner Conductor DC Resistance	:	≤ 11.5 Ω/km @ 20°C
Outer Conductor DC Resistance	:	≤ 13.5 Ω /km @ 20°C
Insulation Resistance	:	5000 MΩ.km
Characteristic Impedance	:	50 Ω ± 3 Ω
Nominal Capacitance	:	83 pF/m
Velocity of Propagation	:	80%
Peak Power	:	5.6 kW
Shielding Effectiveness	:	> 90 dB

Attenuation @20°C

Frequency (MHz)	Attenuation (per 100m)	Attenuation (per 100ft)	Power kW	Frequency (MHz)	Attenuation (per 100m)	Attenuation (per 100ft)	Power kW
30	≤ 4.4 dB	≤ 1.3 dB	1.49	1500	≤ 32.4 dB	≤ 9.9 dB	0.20
50	≤ 5.7 dB	≤ 1.7 dB	1.15	1800	≤ 35.6 dB	≤ 10.9 dB	0.18
150	≤ 9.9 dB	≤ 3.0 dB	0.66	2000	≤ 37.7 dB	≤ 11.5 dB	0.17
220	≤ 12.0 dB	≤ 3.7 dB	0.54	2500	≤ 42.4 dB	≤ 12.9 dB	0.15
450	≤ 17.3 dB	≤ 5.3 dB	0.38	5800	≤ 79.7 dB	≤ 20.4 dB	0.10
900	≤ 24.8 dB	≤ 7.6 dB	0.26				

Certifications & Standards

RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Fca to BS EN 50575:2014+A1:2016

Publication Date: 28/01/2026

Revision Number: 2.0

Written by: GB

Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.