


Technical Document
3183A / BS 6004 Arctic Grade
3 Core 0.75mm² - 2.5mm² PVC Blue

webro

Description: 3183A / BS 6004 3 Core 0.75mm² -
2.5mm² Arctic Grade PVC Blue Sheath



Product Construction

Conductor Material	:	Bare Copper
Conductor Stranding	:	Class 5 to IEC / BS EN 60228
Insulation Material	:	Cold Resistant Polyvinyl Chloride (PVC)
Number of Cores	:	3
Core Colours	:	Brown, Blue, Green/Yellow
Sheath Material	:	Cold Resistant Polyvinyl Chloride (PVC)
Sheath Colour	:	Blue



Mechanical Characteristics

Overall Diameter	:	See Table A
Temperature Range	:	-40°C to +60°C
Bend Radius	:	6 x Overall Diameter
Weight	:	See Table A

Electrical Characteristics

Inner Conductor DC Resistance	:	See Table A
Voltage Rating	:	300/500V
AC Test Voltage	:	2kV

Certifications & Standards

Manufactured to	:	3183A, BS 6004
Flame Retardancy	:	BS EN 60332-1-2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
CE CPR Classification	:	Eca to EN 50575:2014+A1:2016

Part No.	Conductor Size (mm ²)	Nominal OD (mm)	Weight (kg/km)	Nom. Resistance (Ω/km)
320017E-AG-BLU	0.75	6.7	68	26.0
320018E-AG-BLU	1.0	7.0	78	19.5
320020E-AG-BLU	1.5	8.3	110	13.3
320021E-AG-BLU	2.5	10.0	165	7.98

Publication Date: 29/05/2023

Revision Number: 2.0

Written by: GB

Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.