

Technical Document  
2 Fibre OS2 G.657.A2 Tight Buffered  
Duplex MD 302 LSNH Black

webro

Part Number: 33000002005C-BLK-01

Description: 2 Fibre OS2 G.657.A2 Tight Buffered  
Duplex MD 302 LSNH Black



**Product Construction**

Fibre Type	:	OS2, G.657.A2
Number of Fibre	:	2
Colour Code	:	Orange, Blue
Strength Members	:	High Tensile Aramid Yarn
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Black

**Mechanical Characteristics**

Outer Jacket Thickness	:	0.4mm
Overall Diameter	:	2.8mm ± 0.1mm
Temperature Range	:	-5°C to +50°C to EN 60794-1-22-F1
Bend Radius	No Load :	15 x Overall Diameter to EN 60794-1-21-E11a
	Load :	20 x Overall Diameter to EN 60794-1-21-E11b
Weight	:	7.6 kg/km

**Electrical Characteristics**

Nominal Buffer Diameter	:	0.9mm
Maximum Tensile Strength	:	280N to EN 60794-1-21-E1
Maximum Crush Resistance	:	1000N to EN 60794-1-21-E3
Maximum Impact Resistance	:	5Nm to EN 60794-1-21-E4

**Certifications & Standards**

Flame Retardancy	:	BS EN 60332-3-22A
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
CE CPR Classification	:	Cca s1, d0, a1 to EN 50575:2014+A1:2016



Publication Date: 06/09/2024

Revision Number: 2.0

Written by: GB

Authorised by: GB

**Webro Cables & Connectors Ltd**

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK  
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | [www.webro.com](http://www.webro.com)

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.

Technical Document  
2 Fibre OS2 G.657.A2 Tight Buffered  
Duplex MD 302 LSNH Brown

webro

Part Number: 3300000205C-BRN-01

Description: 2 Fibre OS2 G.657.A2 Tight Buffered  
Duplex MD 302 LSNH Brown



**Product Construction**

Fibre Type	:	OS2, G.657.A2
Number of Fibre	:	2
Colour Code	:	Orange, Blue
Strength Members	:	High Tensile Aramid Yarn
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Brown

**Mechanical Characteristics**

Outer Jacket Thickness	:	0.4mm
Overall Diameter	:	2.8mm ± 0.1mm
Temperature Range	:	-5°C to +50°C to EN 60794-1-22-F1
Bend Radius	No Load :	15 x Overall Diameter to EN 60794-1-21-E11a
	Load :	20 x Overall Diameter to EN 60794-1-21-E11b
Weight	:	7.6 kg/km

**Electrical Characteristics**

Nominal Buffer Diameter	:	0.9mm
Maximum Tensile Strength	:	280N to EN 60794-1-21-E1
Maximum Crush Resistance	:	1000N to EN 60794-1-21-E3
Maximum Impact Resistance	:	5Nm to EN 60794-1-21-E4

**Certifications & Standards**

Flame Retardancy	:	BS EN 60332-3-22A
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
CE CPR Classification	:	Cca s1, d0, a1 to EN 50575:2014+A1:2016



Publication Date: 06/09/2024

Revision Number: 2.0

Written by: GB

Authorised by: GB

**Webro Cables & Connectors Ltd**

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK  
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | [www.webro.com](http://www.webro.com)

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.

Technical Document  
2 Fibre OS2 G.657.A2 Tight Buffered  
Duplex MD 302 LSNH White

webro

Part Number: 33000002005C-WHT-01

Description: 2 Fibre OS2 G.657.A2 Tight Buffered  
Duplex MD 302 LSNH White



**Product Construction**

Fibre Type	:	OS2, G.657.A2
Number of Fibre	:	2
Colour Code	:	Orange, Blue
Strength Members	:	High Tensile Aramid Yarn
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	White

**Mechanical Characteristics**

Outer Jacket Thickness	:	0.4mm
Overall Diameter	:	2.8mm ± 0.1mm
Temperature Range	:	-5°C to +50°C to EN 60794-1-22-F1
Bend Radius	No Load :	15 x Overall Diameter to EN 60794-1-21-E11a
	Load :	20 x Overall Diameter to EN 60794-1-21-E11b
Weight	:	7.4 kg/km

**Electrical Characteristics**

Nominal Buffer Diameter	:	0.9mm
Maximum Tensile Strength	:	280N to EN 60794-1-21-E1
Maximum Crush Resistance	:	1000N to EN 60794-1-21-E3
Maximum Impact Resistance	:	5Nm to EN 60794-1-21-E4

**Certifications & Standards**

Flame Retardancy	:	BS EN 60332-3-22A
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
CE CPR Classification	:	Cca s1, d0, a1 to EN 50575:2014+A1:2016



Publication Date: 06/09/2024

Revision Number: 2.0

Written by: GB

Authorised by: GB

**Webro Cables & Connectors Ltd**

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK  
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | [www.webro.com](http://www.webro.com)

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.