

Technical Document
2 Fibre OS2 G.657.A1 Tight Buffered
Duplex MD 302 LSNH Black

webro

Part Number: 330600-BLK

Description: 2 Fibre OS2 G.657.A1 Tight Buffered
Duplex MD 302 LSNH Black



Product Construction

Fibre Type	:	OS2, G.657.A1
Number of Fibre	:	2
Colour Code	:	Orange, Blue
Strength Members	:	High Tensile Aramid Yarn
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Black

Mechanical Characteristics

Outer Jacket Thickness	:	0.4mm
Overall Diameter	:	2.8mm ± 0.1mm
Temperature Range	:	-5°C to +50°C to EN 60794-1-22-F1
Bend Radius	No Load :	15 x Overall Diameter to EN 60794-1-21-E11a
	Load :	20 x Overall Diameter to EN 60794-1-21-E11b
Weight	:	7.4 kg/km

Electrical Characteristics

Nominal Buffer Diameter	:	0.9mm
Maximum Tensile Strength	:	280N to EN 60794-1-21-E1
Maximum Crush Resistance	:	1000N to EN 60794-1-21-E3
Maximum Impact Resistance	:	5Nm to EN 60794-1-21-E4

Certifications & Standards

Flame Retardancy	:	BS EN 60332-3-22A
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
CE CPR Classification	:	Eca to EN 50575:2014+A1:2016



Publication Date: 04/05/2023

Revision Number: 2.0

Written by: GB

Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.

Technical Document
2 Fibre OS2 G.657.A1 Tight Buffered
Duplex MD 302 LSNH Brown

webro

Part Number: 330600-BRN

Description: 2 Fibre OS2 G.657.A1 Tight Buffered
Duplex MD 302 LSNH Brown



Product Construction

Fibre Type	:	OS2, G.657.A1
Number of Fibre	:	2
Colour Code	:	Orange, Blue
Strength Members	:	High Tensile Aramid Yarn
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Brown

Mechanical Characteristics

Outer Jacket Thickness	:	0.4mm
Overall Diameter	:	2.8mm ± 0.1mm
Temperature Range	:	-5°C to +50°C to EN 60794-1-22-F1
Bend Radius	No Load :	15 x Overall Diameter to EN 60794-1-21-E11a
	Load :	20 x Overall Diameter to EN 60794-1-21-E11b
Weight	:	7.4 kg/km

Electrical Characteristics

Nominal Buffer Diameter	:	0.9mm
Maximum Tensile Strength	:	280N to EN 60794-1-21-E1
Maximum Crush Resistance	:	1000N to EN 60794-1-21-E3
Maximum Impact Resistance	:	5Nm to EN 60794-1-21-E4

Certifications & Standards

Flame Retardancy	:	BS EN 60332-3-22A
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
CE CPR Classification	:	Eca to EN 50575:2014+A1:2016



Publication Date: 04/05/2023

Revision Number: 2.0

Written by: GB

Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.

Technical Document
2 Fibre OS2 G.657.A1 Tight Buffered
Duplex MD 302 LSNH White

webro

Part Number: 330600-WHT

Description: 2 Fibre OS2 G.657.A1 Tight Buffered
Duplex MD 302 LSNH White



Product Construction

Fibre Type	:	OS2, G.657.A1
Number of Fibre	:	2
Colour Code	:	Orange, Blue
Strength Members	:	High Tensile Aramid Yarn
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	White

Mechanical Characteristics

Outer Jacket Thickness	:	0.4mm
Overall Diameter	:	2.8mm ± 0.1mm
Temperature Range	:	-5°C to +50°C to EN 60794-1-22-F1
Bend Radius	No Load :	15 x Overall Diameter to EN 60794-1-21-E11a
	Load :	20 x Overall Diameter to EN 60794-1-21-E11b
Weight	:	7.4 kg/km

Electrical Characteristics

Nominal Buffer Diameter	:	0.9mm
Maximum Tensile Strength	:	280N to EN 60794-1-21-E1
Maximum Crush Resistance	:	1000N to EN 60794-1-21-E3
Maximum Impact Resistance	:	5Nm to EN 60794-1-21-E4

Certifications & Standards

Flame Retardancy	:	BS EN 60332-3-22A
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
CE CPR Classification	:	Eca to EN 50575:2014+A1:2016



Publication Date: 04/05/2023

Revision Number: 2.0

Written by: GB

Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.