


Part Number: 350303C-LSNH-GRN  
Description: KNX 2pair 0.8mm Screened Low  
Smoke Non-Halogen (LSNH) Green



#### Product Construction

Conductor Material	:	Bare Copper
Conductor Stranding	:	Solid, 1/0.80mm
Insulation Material	:	Polyethylene (PE)
Number of Pairs	:	2
Core Colours	:	Black, Red; Yellow, White
Drain Wire	:	Tinned Copper, 1/0.80mm
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Green



#### Mechanical Characteristics

Overall Diameter	:	5.6mm ± 0.35mm
Temperature Range	Fixed	-15°C to +80°C
	Flexing	0°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	52 kg/km

#### Electrical Characteristics

Inner Conductor DC Resistance	:	≤ 37.5 Ω/km
Capacitance, Data Core to Core	:	< 100 pF/m ± 10
Max. Surface Transfer Impedance	:	200 MΩ /m (f <10MHz)
Insulation Resistance @ 20°C	:	≥ 200 MΩ *M
Working Voltage	:	50V
Test Voltage	:	800V

#### Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2, BS EN 60332-3-24C, CEI 20-35/1-2, CEI 20-22/3-4
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Cca s1b, d1, a1 to BS EN 50575:2014+A1:2016

CEDIA<sup>®</sup>  
MEMBER

Publication Date: 26/10/2022  
Revision Number: 2.0  
Written by: GB  
Authorised by: GB

#### Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK  
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | [www.webro.com](http://www.webro.com)

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.