


Part Number: 350303E-LSNH-GRN-01  
Description: KNX 2pair 0.8mm Screened Low  
Smoke Non-Halogen (LSNH) Green



**Product Construction**

Conductor Material	:	Bare Copper
Conductor Stranding	:	Solid, 1/0.80mm
Insulation Material	:	Polyethylene (PE)
Number of Pairs	:	2
Core Colours	:	Black, Red; Yellow, White
Drain Wire	:	Tinned Copper, 1/0.40mm
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Fillers	:	Cotton Fillers
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Green



**Mechanical Characteristics**

Overall Diameter	:	6.6mm ± 0.35mm
Temperature Range	Fixed	-20°C to +70°C
	Flexing	0°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	52 kg/km

**Electrical Characteristics**

Inner Conductor DC Resistance	:	≤ 36.6 Ω/km
Capacitance, Data	Core to Core	52 pF/m ± 10
	Core to Screen	104 pF/m ± 20
Impedance	:	92 Ω ± 10
Insulation Resistance @ 20°C	:	≥ 200 M Ω *M
Voltage Rating	:	300/500V

**Certifications & Standards**

Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016

CEDIA<sup>®</sup>  
MEMBER



Publication Date: 14/11/2022  
Revision Number: 2.0  
Written by: GB  
Authorised by: GB

**Webro Cables & Connectors Ltd**

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK  
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | [www.webro.com](http://www.webro.com)

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.