

Part Number: 390151E-LSNH-WHT

Description: WEB 16/22 White 1pair 22awg +
1pair 16awg LSNH White



Product Construction

Alternative to Lutron	:	QSH-CBL-M-500
Data		
Conductor Material	:	Bare Copper
Conductor Stranding	:	22awg, 16/0.16mm
Insulation Material	:	Foamed Polyethylene (FPE)
Number of Pairs	:	1
Core Colours	:	White, Violet
Drain Wire	:	Tinned Copper, 24awg
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%

Power

Conductor Material	:	Bare Copper
Conductor Stranding	:	16awg, 26/0.25mm
Insulation Material	:	Polyethylene (PE)
Number of Cores	:	2
Core Colours	:	Black, Red

Overall Construction

Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	White

Mechanical Characteristics

Overall Diameter	:	6.2mm ± 0.2mm
Temperature Range	Fixed	-20°C to +70°C
	Flexing	0°C to +60°C
Bend Radius	:	10 x Overall Diameter
Weight	:	69 kg/km

Electrical Characteristics

Conductor DC Resistance @ 20°C	:	Data	≤ 55.4 Ω/km
	:	Power	≤ 13.7 Ω/km
Capacitance, Data	Core to Core	:	50 pF/m ± 10
	Core to Screen	:	100 pF/m ± 20
Insulation Resistance @ 20°C	:		≥ 5000 M Ω*km
Voltage Rating	:		300/300V

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016



CEDIA[®]
MEMBER

Publication Date: 26/10/2022
Revision Number: 2.0
Written by: GB
Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.