

Technical Document
Alternative to Belden 8723
2pair 22awg LSNH Grey

webro

Part Number: 428723C-LSNH-SLT

Description: Alternative to Belden 8723 2pair
22awg Individual Foil Screened Pairs LSNH Grey



Product Construction

Alternative to Belden	:	8723 NH
Conductor Material	:	Tinned Copper
Conductor Stranding	:	22awg; 7/0.25mm
Insulation Material	:	Low Smoke Non-Halogen (LSNH)
Number of Pairs	:	2
Core Colours	:	Black/Red, Green/White
Screening 1	:	Aluminium Foil Around Each Pair
Screening 1 Coverage	:	>100%
Drain Wire	:	Tinned Copper, 24awg Stranded
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Grey



Mechanical Characteristics

Overall Diameter	:	4.3mm ± 0.20mm
Temperature Range	Fixed	-10°C to +70°C
	Flexing	+5°C to +40°C
Bend Radius	:	10 x Overall Diameter
Weight	:	33 kg/km

Electrical Characteristics

Conductor DC Resistance @20°C	:	≤ 50.10 Ω/km
Capacitance	Core to Core	90 pF/m ± 15
	Core to Screen	118 pF/m ± 25
Insulation Resistance @ 20°C	:	≥ 200 MΩ *M
Voltage Rating	:	50V

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Cca s1a, d0, a1 to BS EN 50575:2014+A1:2016

Publication Date: 15/05/2024

Revision Number: 2.0

Written by: GB

Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.