

Technical Document  
Alternative to Belden 8723  
2pair 22awg LSF Grey

webro

Part Number: 428723E

Description: Alternative to Belden 8723 2pair  
22awg Individual Foil Screened Pairs LSF Grey



**Product Construction**

Alternative to Belden	:	8723
Conductor Material	:	Tinned Copper
Conductor Stranding	:	22awg; 7/0.25mm
Insulation Material	:	Solid Polyethylene (SPE)
Number of Pairs	:	2
Core Colours	:	Black/Red, Green/White
Screening 1	:	Aluminium Foil Around Each Pair
Screening 1 Coverage	:	>100%
Drain Wire	:	Tinned Copper, 24awg Stranded
Sheath Material	:	Low Smoke & Fume (LSF)
Sheath Colour	:	Grey



**Mechanical Characteristics**

Overall Diameter	:	4.2mm ± 0.20mm
Temperature Range	Fixed	-10°C to +70°C
	Flexing	0°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	33 kg/km

**Electrical Characteristics**

Conductor DC Resistance @20°C	:	≤ 60.2 Ω/km
Capacitance	Core to Core	83 pF/m ± 15
	Core to Screen	162 pF/m ± 25
Insulation Resistance @ 20°C	:	≥ 200 MΩ *M
Voltage Rating	:	300V

**Certifications & Standards**

Flame Retardancy	:	BS EN 60332-1-2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016

CEDIA<sup>®</sup>  
MEMBER

Publication Date: 28/11/2022  
Revision Number: 2.0  
Written by: GB  
Authorised by: GB

**Webro Cables & Connectors Ltd**

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK  
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | [www.webro.com](http://www.webro.com)

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.