


Technical Document
Alternative to Belden 8761
1pair 22awg LSF Grey

webro

Part Number: 428761E

Description: Alternative to Belden 8761 1pair
22awg Overall Foil Screened LSF Grey



Product Construction

Alternative to Belden	:	8761
Conductor Material	:	Tinned Copper
Conductor Stranding	:	22awg; 7/0.25mm
Insulation Material	:	Polyethylene (PE)
Number of Pairs	:	1
Core Colours	:	Clear & Black
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Drain Wire	:	Tinned Copper, 22awg Stranded
Sheath Material	:	Low Smoke & Fume (LSF)
Sheath Colour	:	Grey



Mechanical Characteristics

Overall Diameter	:	4.45mm ± 0.30mm
Temperature Range	Fixed	-10°C to +70°C
	Flexing	0°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	24 kg/km

Electrical Characteristics

Conductor DC Resistance @20°C	:	≤ 58.6 Ω/km
Capacitance	Core to Core	79 pF/m ± 15
	Core to Screen	154 pF/m ± 25
Insulation Resistance @ 20°C	:	≥ 200 MΩ *M
Voltage Rating	:	300V

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016

CEDIA[®]
MEMBER

Publication Date: 28/11/2022
Revision Number: 2.0
Written by: GB
Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.