

Technical Document
Alternative to Belden 9502
2pair 24awg LSF Grey

webro

Part Number: 429502E

Description: Alternative to Belden 9502 2pair
24awg Overall Foil Screened LSF Grey



Product Construction

Alternative to Belden	:	9502
Conductor Material	:	Tinned Copper
Conductor Stranding	:	24awg; 7/0.20mm
Insulation Material	:	Low Smoke & Fume (LSF)
Number of Pairs	:	2
Core Colours	:	Black/Red, Black/White
Drain Wire	:	Tinned Copper, 24awg Stranded
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Sheath Material	:	Low Smoke & Fume (LSF)
Sheath Colour	:	Grey



Mechanical Characteristics

Overall Diameter	:	5.6mm ± 0.20mm
Temperature Range	Fixed	-10°C to +70°C
	Flexing	0°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	39 kg/km

Electrical Characteristics

Conductor DC Resistance @20°C	:	≤ 97.0 Ω/km
Capacitance	Core to Core	131 pF/m ± 20
	Core to Screen	243 pF/m ± 35
Insulation Resistance @ 20°C	:	≥ 200 M Ω *M
Voltage Rating	:	300V

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
Suitable Protocol	:	RS 232
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
CE CPR Classification	:	Eca to EN 50575:2014+A1:2016

CEDIA[®]
MEMBER

Publication Date: 13/05/2024
Revision Number: 2.0
Written by: GB
Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.