

Technical Document  
Alternative to Belden 9504  
4pair 24awg LSNH Grey

webro

Part Number: 429504B-LSNH

Description: Alternative to Belden 9504 4pair  
24awg Overall Foil Screened LSNH Grey



**Product Construction**

Alternative to Belden	:	9504NH, 9504ELW
Conductor Material	:	Tinned Copper
Conductor Stranding	:	24awg; 7/0.20mm
Insulation Material	:	Low Smoke Non-Halogen (LSNH)
Number of Pairs	:	4
Core Colours	:	Black/Red, Black/White, Black/Green, Black/Blue
Drain Wire	:	Tinned Copper, 24awg Stranded
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Grey



**Mechanical Characteristics**

Overall Diameter	:	6.8mm ± 0.20mm
Temperature Range	Fixed	-10°C to +70°C
	Flexing	0°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	48 kg/km

**Electrical Characteristics**

Conductor DC Resistance @20°C	:	≤ 56.0 Ω/km
Insulation Resistance @ 20°C	:	≥ 200 MΩ *M
Voltage Rating	:	300/500V

**Certifications & Standards**

Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
Suitable Protocol	:	RS 232
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	B2ca s1a, d0, a1 to BS EN 50575:2014+A1:2016

Publication Date: 15/05/2025

Revision Number: 2.0

Written by: GB

Authorised by: GB

**Webro Cables & Connectors Ltd**

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK  
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | [www.webro.com](http://www.webro.com)

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.