


Technical Document
Alternative to Belden 9534
4core 24awg LSF Grey

webro

Part Number: 429534E

Description: Alternative to Belden 9534 4core
24awg Overall Foil Screened LSF Grey



Product Construction

Alternative to Belden	:	9534
Conductor Material	:	Tinned Copper
Conductor Stranding	:	24awg; 7/0.20mm
Insulation Material	:	Polyvinyl Chloride (PVC)
Number of Cores	:	4
Core Colours	:	Black, White, Red, Green
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Drain Wire	:	Tinned Copper, 24awg Stranded
Sheath Material	:	Low Smoke & Fume (LSF)
Sheath Colour	:	Grey



Mechanical Characteristics

Overall Diameter	:	4.7mm ± 0.20mm
Temperature Range	Fixed	-20°C to +70°C
	Flexing	0°C to +70°C
Bend Radius	:	15 x Overall Diameter
Weight	:	30 kg/km

Electrical Characteristics

Conductor DC Resistance @20°C	:	≤ 90.9 Ω/km
Capacitance	Core to Core	108 pF/m ± 20
	Core to Screen	213 pF/m ± 35
Insulation Resistance @ 20°C	:	≥ 200 M Ω *M
Voltage Rating	:	300V

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
Suitable Protocol	:	RS 232
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016

CEDIA[®]
MEMBER

Publication Date: 23/05/2024
Revision Number: 2.0
Written by: GB
Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.