

Technical Document  
Alternative to Belden 9540  
10core 24awg External Grade PE Black

webro

Part Number: 429540F-PE-BLK

Description: Alternative to Belden 9540 10core  
24awg Overall Foil Screened External Grade PE Black



**Product Construction**

Alternative to Belden	:	9540
Conductor Material	:	Tinned Copper
Conductor Stranding	:	24awg; 7/0.20mm
Insulation Material	:	Polyvinyl Chloride (PVC)
Number of Cores	:	10
Core Colours	:	Black, White, Red, Green, Brown Blue, Orange, Yellow, Violet, Grey
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Drain Wire	:	Tinned Copper, 24awg Stranded
Sheath Material	:	Polyethylene (PE)
Sheath Colour	:	Black



**Mechanical Characteristics**

Overall Diameter	:	6.4mm ± 0.20mm
Temperature Range	Fixed	-20°C to +70°C
	Flexing	0°C to +70°C
Bend Radius	:	15 x Overall Diameter
Weight	:	56 kg/km

**Electrical Characteristics**

Conductor DC Resistance @20°C	:	≤ 104.2 Ω/km
Capacitance	Core to Core	108 pF/m ± 20
	Core to Screen	213 pF/m ± 35
Insulation Resistance @ 20°C	:	≥ 200 MΩ *M
Voltage Rating	:	300V

**Certifications & Standards**

RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Fca to EN 50575:2014+A1:2016

Publication Date: 29/09/2023

Revision Number: 2.0

Written by: GB

Authorised by: GB

**Webro Cables & Connectors Ltd**

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK  
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | [www.webro.com](http://www.webro.com)

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.