

Part Number: 470020E-BLK

Description: TZC 75024 75ohm Coaxial Cable PVC
Black



Product Construction

Conductor Material	:	Bare Copper
Conductor Stranding	:	Solid, 1/0.31mm
Dielectric Material	:	Solid Polyethylene (SPE)
Dielectric Diameter	:	1.95mm ± 0.10
Screening 1	:	Tinned Copper Wire Braid
Screening 1 Coverage	:	> 93% ± 3
Screening 2	:	Tinned Copper Wire Braid
Screening 2 Coverage	:	> 87% ± 3
Sheath Material	:	Polyvinyl Chloride (PVC)
Sheath Colour	:	Black



Mechanical Characteristics

Overall Diameter	:	3.55mm ± 0.20mm
Temperature Range	Fixed	-15°C to +70°C
	Fixed	-5°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	26 kg/km

Electrical Characteristics

Inner Conductor DC Resistance	:	≤ 236.0 Ω/km @ 20°C
Outer Conductor DC Resistance	:	≤ 16.0 Ω/ km @ 20°C
Impedance	:	75 Ω ± 4
Nominal Capacitance	:	67 pF/m
Velocity of Propagation	:	66%
Insulation Resistance @ 20°C	:	≥ 500 M Ω*KM
Return Loss @ 1MHz-200MHz	:	> 30 dB
Voltage Rating	:	30v

Attenuation @20°C

Frequency (MHz)	Attenuation (per 100m)	Frequency (MHz)	Attenuation (per 100m)
1	≤ 2.2 dB	45	≤ 15.8 dB
5	≤ 4.8 dB	100	≤ 23.8 dB
10	≤ 7.2 dB	155	≤ 30.0 dB

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016

Publication Date: 23/01/2023

Revision Number: 2.0

Written by: GB

Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.