

Technical Document  
RG59 B/U 75ohm Coaxial Cable  
PVC Black

webro

Part Number: 490004E-BLK

Description: RG59 B/U 75ohm Coaxial Cable PVC  
Black



**Product Construction**

Conductor Material	:	Copper Clad Steel
Conductor Stranding	:	Solid, 1/0.58mm
Dielectric Material	:	Solid Polyethylene (SPE)
Dielectric Diameter	:	3.70mm ± 0.10
Screening 1	:	Plain Copper Wire Braid
Screening 1 Coverage	:	> 80% ± 3
Sheath Material	:	Polyvinyl Chloride (PVC)
Sheath Colour	:	Black

**Mechanical Characteristics**

Overall Diameter	:	6.1mm ± 0.20mm
Temperature Range	Fixed	-20°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	47 kg/km

**Electrical Characteristics**

Inner Conductor DC Resistance	:	≤ 220 Ω/km @ 20°C
Outer Conductor DC Resistance	:	≤ 16 Ω/ km @ 20°C
Impedance	:	75 Ω ± 3
Nominal Capacitance	:	67 pF/m
Velocity of Propagation	:	66%
Insulation Resistance @ 20°C	:	≥ 1000 M Ω*M
Maximum Operating Voltage	:	3.7 kV RMS
Structural Return Loss DC	:	> 20dB @ 1GHz

**Attenuation @20°C**

Frequency (MHz)	Attenuation (per 100m)	Frequency (MHz)	Attenuation (per 100m)
50	≤ 8.5 dB	800	≤ 35.8 dB
100	≤ 11.8 dB	860	≤ 37.2 dB
200	≤ 16.5 dB	1000	≤ 39.5 dB
450	≤ 26.0 dB		

**Certifications & Standards**

Flame Retardancy	:	BS EN 60332-1-2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to EN 50575:2014+A1:2016



Publication Date: 23/01/2023

Revision Number: 2.0

Written by: GB

Authorised by: GB

**Webro Cables & Connectors Ltd**

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK  
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | [www.webro.com](http://www.webro.com)

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.