

BPEO Fibre Closure EVOLV PUSHLOK BPEO S1 08P 08F

CORNING

Part Number:
B1-08P-D00-02A-PG08

Fibre Closures BPEO are designed with flexibility in application in mind. Available in a range of sizes, they can be deployed above grade (pole, facade) or below grade (manhole, handhole). These closures can be used for fibre-to-the-home (FTTH) deployments and any type of optical fibre cable deployment in the outside plant. Mechanical and tool free: Easy to re-enter and close; integrated sealing gasket keeps water out. The built-in seals of the BPEO in conjunction with the latch mechanism ensure that the closure remains watertight even after frequent use. The sealing gasket requires no replacement and no addition of sealant material, even after several open/close operations.

Features and Benefits

Fibre organiser (ramp or flat)

Enables fibre and tube management, supports single fibre management

Tool-less opening and closing

Quick-and-easy installation

Use of ECAM: External Cable Assembly Module



Easy and fast addition of loop and drop cables, without disrupting already installed fibre and protecting the fibre organiser of any debris

Integrated sealing gasket

Ensures water tightness and remains functional even after several open/close operations

IP68 design

Reliable and watertight with an integrated valve for flash on-site testing



BPEO Fibre Closure EVOLV PUSHLOK BPEO S1 08P 08F



Specifications

General Specifications

Application	Aerial / Manhole
Environment	Outdoor
Cable type	Round
Mounting Type	Anchoring
Product type	Preconnected Closure
Branching	Yes
Brand	BPEO

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Environmental Conditions

Temperature range, operation	-40 °C to 65 °C
------------------------------	-----------------

Design

Splitter support	Yes
Buffer storage	Installed
Capacity (number of splices)	84
Closure shape	Dome
Closure type	Canister
Distribution cable port count	2
Distribution Port Count	2
Drop cable type	SST flat or round
Fibre Capacity	84
Fibre Type	Standard bend radius G652D

BPEO Fibre Closure EVOLV PUSHLOK BPEO S1 08P 08F



Design	
Heat shrink splice count per SE tray	12
Heat shrink splice count per tray	12
Input cable type	External cable assembly module (ECAM)
Main cable diameter	5-18 mm
Main cable oval port count	1
Maximum number of fibers	12
Max number of trays	7
Maximum splice fiber capacity	84
Maximum tray count	7
Number of Cable Entries	11
Number of distribution/drop cables ports	2
Number of Connector Adapters	8
Number of ports - cut	1
Number of splice trays	7
Number of splice trays preloaded	2
Pigtail class	Grade B
Sealing type	Rubber Gasket
Test valve	Included
Trays capacity	7
Number of single-fibre ports, SC APC connector	8
Number of pigtails	8

Ordering Information	
Product Number	B1-08P-D00-02A-PG08
Length	382 mm
Package contents	"Pushlok ECAM Convertor , ECAM D18 (or 2x ECAM S12)"
Width	204 mm
Depth	92 mm

BPEO Fibre Closure EVOLV PUSHLOK BPEO S1 08P 08F

The CORNING logo is a dark blue square with the word "CORNING" in white, uppercase, sans-serif font centered within it.

Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2023 Corning Optical Communications. All rights reserved.